


CHARTERHOUSE

LIMESTONE • TUMBLED

Rustic yet refined, this very hard limestone contains green and charcoal hints within its tonal range - the sort of colours that give you plenty of options for matching to other interior materials.



FORMAT (CM)

60 x Random x 2

AVAILABILITY

Usually in stock

PACK QUANTITY

20m²

Suitable for interior floors,
sealing required.

TECHNICAL DATA

Petrographic Description

Dark bluish cream to pale bluish beige with occasional, unevenly distributed, pale grey/brown and white, irregular to elongate sparry calcite and sporadically relict bioclasts, up to 2mm across and 5mm long and commonly less than 1mm across and 2mm long, predominantly fine to very fine grained and occasionally medium, fresh LIMESTONE, well to very well compacted, generally hard and robust (subjective assessment). Veins and joints, up to 1mm and commonly less than 0.3mm wide, were infilled with sparry calcite and ran mainly across the thickness and occasionally parallel to principal surfaces along the thickness of the slab sample.

TEST	STANDARD	RESULT
Apparent Density	BS EN 1936 : 2006	2670kg/m ³
Open Porosity	BS EN 1936 : 2006	1.2%
Water Absorption at Atmospheric Pressure	BS EN 13755 : 2008	0.4%
Flexural Strength (3 Point)	BS EN 12372 : 2006	17.4MPa
Frost Resistance (56 Cycles)	BS EN 12371 : 2010	16.0MPa
Abrasion Resistance	BS EN 14157 : 2004	18.5mm
Thermal Shock Resistance	BS EN 14066 : 2013	16.2MPa
Slip Resistance (Dry)	BS EN 14231 : 2003	PTV 48
Slip Resistance (Wet)	BS EN 14231 : 2003	PTV 9

- ✓ Suitable for use with underfloor heating
- ✓ Suitable for use in freezing temperatures

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.