

WELTZNER

LIMESTONE • SATINO

This is a strikingly-textured, hard limestone with lively colour tones ranging from steel grey to putty and plenty of character in the shell markings and veins. It's an ideal option for larger spaces which do justice to the stone's full beauty.



60 X RANDOM X 2CM



PARQUET


FORMAT (CM)

Parquet: 9 x 40 x 2
60 x Random x 2

AVAILABILITY

Usually in stock
Usually in stock

Suitable for interior floors,
sealing required.



TECHNICAL DATA

Petrographic Details

Pale grey to bluish grey with frequent cream to yellowish cream skeletal bioclastic debris, up to 25mm across and 30mm long, coarse to fine grained limestone, hard to very hard and generally indurated (subjective assessment) with sporadic irregular voids less than 1mm across, mainly associated with frequent joints/infilled cracks running along and across the thickness of the sample.

TEST	STANDARD	RESULT
Apparent Density	BS EN 1936 : 2006	2540kg/m ³
Open Porosity	BS EN 1936 : 2006	6.4%
Water Absorption at Atmospheric Pressure	BS EN 13755 : 2008	2.2%
Flexural Strength (3 Point)	BS EN 12372 : 2006	15.1MPa
Frost Resistance (56 Cycles)	BS EN 12371 : 2010	18.1MPa
Abrasion Resistance	BS EN 14157 : 2004	20.5mm
Thermal Shock Resistance	BS EN 14066 : 2013	16.8MPa
Slip Resistance (Dry)	BS EN 14231 : 2003	PTV 60
Slip Resistance (Wet)	BS EN 14231 : 2003	PTV 23

✓ Suitable for use with underfloor heating

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

PRODUCT NOTES

This product is prone to efflorescence. To avoid this, store in a dry area, and use rapid or semi-rapid set adhesive, such as our Sarsen Home Premium Semi-Rapid Adhesive.