

ZUBER

LIMESTONE • TUMBLED

This is a charcoal-toned limestone with a lovely cloudy undertone. We often mix it with a cream limestone in a chequerboard pattern, but it makes a very striking statement on its own.



SHOWN WITH BERGAMO TUMBLED

FORMAT (CM)

40 x 40 x 1.3

AVAILABILITY

Usually in stock

Suitable for interior walls
and floors, sealing required.



TECHNICAL DATA

| TEST | STANDARD | RESULT |
|--|--------------------|-----------------------|
| Apparent Density | BS EN 1936 : 2006 | 2662kg/m ³ |
| Water Absorption at Atmospheric Pressure | BS EN 13755 : 2008 | 0.26% |
| Flexural Strength (3 Point) | BS EN 12372 : 2006 | 11MPa |
| Slip Resistance (Dry) | BS EN 14231 : 2003 | PTV 44 |
| Slip Resistance (Wet) | BS EN 14231 : 2003 | PTV 23 |

✓ Suitable for use with underfloor heating

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

PRODUCT NOTES

This product is prone to efflorescence. To avoid this, store in a dry area, and use rapid or semi-rapid set adhesive, such as our Sarsen Home Premium Semi-Rapid Adhesive.