

# FOLLY

PORCELAIN • MATT

A nod to the arts and crafts movement, but updated in a playful contemporary way, Folly is an undeniable statement, thanks to the careful detail and organic melange effect.



FORMAT (CM)

20 x 23 x 0.8

SOLD BY

10 pieces (0.33m<sup>2</sup>)

AVAILABILITY


Usually in stock

Suitable for interior and domestic exterior walls and floors.

Slip rating: R10, PTV +36 when wet



## EXAMPLE TILES



MOSS



LAKE



SAND

## TECHNICAL DATA

| TEST   | STANDARD        | RESULT                     |
|--|-----------------|----------------------------|
| Dimensional Tolerances                                   | EN ISO 10545-2  | Within standard tolerances |
| Water Absorption   | EN ISO 10545-3  | <0.5%                      |
| Modulus of Rupture                                       | EN ISO 10545-4  | 35N/mm <sup>2</sup>        |
| Breaking Strength  | EN ISO 10545-4  | >1300N                     |
| Resistance to Crazeing                                   | EN ISO 10545-11 | Resistant                  |
| Frost Resistance   | EN ISO 10545-12 | Resistant                  |
| Chemical Resistance - High Concentrations                | EN ISO 10545-13 | GHA                        |
| Chemical Resistance - Households/Swimming Pool Chemicals | EN ISO 10545-13 | GA                         |
| Stain Resistance   | EN ISO 10545-14 | 5                          |
| Resistance to Fire                                       | EN 9239-1       | A1                         |
| Slip Rating  | DIN 51130       | Class 2                    |
| Slip Rating - Barefoot                                   | DIN 51130       | R9                         |
| Slip Rating  | BS 7976-2       | PTV 61 (Dry) 41 (Wet)      |

Rectified: YES  NO

**For any further information or advice, please contact our team.**

## INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to our 'Understanding Unrectified Porcelain Tiles' sheet on our website for product installation advice.

## PRODUCT NOTES

Medium slip risk: This should not be used on pool surrounds and should be kept clean to maintain slip resistance.