

KINFOLK

PORCELAIN • BRUSHED

Creating the effect of slatted wood panelling but hardy enough for use in any area, these tiles give an undeniably elegant linear feel.



EBONY (WALL) SHOWN WITH CHARMOT



NUT



WHITE SHOWN WITH STUCCO BLUE & HIMALAYA CRYSTAL



TEAK SHOWN WITH ASCOLI GRIGIO



MAPLE SHOWN WITH ASCOLI AVORIO



ASH GREY

FORMAT (CM)

60 x 120 x 1


SOLD BY

2 pieces (1.44m²)

AVAILABILITY

Usually in stock

Suitable for interior walls and floors.
Slip rating: R9



V2

WHITE, MAPLE,
ASH GREY, EBONY



V3


NUT,
TEAK



MAPLE



NUT



TEAK



WHITE



ASH GREY



EBONY

TECHNICAL DATA

TEST	STANDARD	RESULT
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	0.3%
Modulus of Rupture	EN ISO 10545-4	35N/mm ²
Breaking Strength	EN ISO 10545-4	1300N
Moisture Expansion	EN ISO 10545-10	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - High Concentrations	EN ISO 10545-13	GHA
Chemical Resistance - Low Concentration	EN ISO 10545-13	GLA
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	GA
Stain Resistance	EN ISO 10545-14	5
Resistance to Fire	EN 9239-1	A1
Slip Rating	DIN 51130	Class 1
Slip Rating - Barefoot	DIN 51130	R10
Slip Rating	BS 7976-2	PTV +36 (Wet)
Dynamic Coefficient of Friction	ANSI A137	≥0.42

Rectified: YES NO

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.