

OSTERLEY

PORCELAIN • TEXTURED

The ground floor at Osterley Park in Middlesex displays an iconic chequerboard limestone floor, worn over the years by the passage of scullery maids and footmen. Our Osterley porcelain tiles authentically replicate this aged look, but with all the practicality and low maintenance of porcelain, and an R11 slip rating for use indoors and out.



OSTERLEY WHITE SQUARE AND BLACK SQUARE



WHITE BRICK AND BLACK BRICK



WHITE BRICK (FLOOR)
SHOWN WITH WIGHTWICK AZURE

OPTION	FORMAT (CM)	SOLD BY	AVAILABILITY	Suitable for interior and exterior walls and floors. Slip rating: R11, PTV +36
BRICK	11 x 22.5 x 1	20 pieces (0.495m ²)	Usually in stock	
SQUARE	22.5 x 22.5 x 1	20 pieces (1.012m ²)	Usually in stock	





TECHNICAL DATA

TEST	STANDARD	RESULT
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	0.19%
Modulus of Rupture	EN ISO 10545-4	39N/mm ²
Breaking Strength	EN ISO 10545-4	2050N
Superficial Abrasion Resistance	EN ISO 10545-7	Class 4
Resistance to Cracking	EN ISO 10545-11	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Stain Resistance	EN ISO 10545-14	Class A
Resistance to Fire	EN 9239-1	A1
Hardness (MOHS)	UNE 67101	9
Slip Rating	DIN 51130	Class 3
Slip Rating - Barefoot	DIN 51130	R11

Rectified: YES NO

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to our 'Understanding Unrectified Porcelain Tiles' sheet on our website for product installation advice. Please note that we recommend the use of our Sarsen Home Porcelain Pre-Grout Barrier with this product to avoid any grout stains on the tile surface.

PRODUCT NOTES

These tiles are non-rectified, so to achieve a chequerboard effect, wider grout joints are needed.