


CARPENTER

PORCELAIN - MATT

Previously known as Woodchester

This beautifully varied wood effect porcelain tile has all the markings and colours of a real oak floor; with colour options mimicking traditional wood finishes.



RICH



NATURAL

FORMAT (CM)

SOLD BY

AVAILABILITY

NOTES

20 x 120 x 0.95

4 pieces (0.96m²)

Usually in stock

Suitable for interior walls and floors.

CA' PIETRA

CAPIETRA.COM



NATURAL



RICH

TECHNICAL DATA

| TEST | STANDARD | RESULT |
|--|-----------------|---------------------------------------|
| Sizing | - | 15 |
| Dimensional Tolerances | EN ISO 10545-2 | Within standard tolerances |
| Water Absorption | EN ISO 10545-3 | ≤0.5% |
| Modulus of Rupture | EN ISO 10545-4 | ≥35N/mm ² |
| Breaking Strength | EN ISO 10545-4 | ≥1300N |
| Deep Abrasion Resistance | EN ISO 10545-6 | ≤175mm ³ |
| Linear Thermal Expansion | EN ISO 10545-8 | ≤9.0x10 ⁻⁶ C ⁻¹ |
| Thermal Shock Resistance | EN ISO 10545-9 | Resistant |
| Frost Resistance | EN ISO 10545-12 | Resistant |
| Chemical Resistance - High Concentrations | EN ISO 10545-13 | UHA |
| Chemical Resistance - Low Concentration | EN ISO 10545-13 | ULA |
| Chemical Resistance - Households/Swimming Pool Chemicals | EN ISO 10545-13 | UA |
| Stain Resistance | EN ISO 10545-14 | 3 |
| Resistance to Fire | EN 9239-1 | A1 |
| Slip Rating - Barefoot | DIN 51130 | R9 |
| Dynamic Coefficient of Friction | ANSI A137 | >0.40 |

Rectified: YES NO

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

