


CHATHAM

PORCELAIN - MATT

Previously known as Southwold

These classic wood effect porcelain tiles look equally as stylish in a bathroom as they do a hallway. Open up a home by laying them throughout the whole ground floor of a project.



FORMAT (CM)

SOLD BY

AVAILABILITY

NOTES

9.8 x 50 x 0.9

16 pieces (0.784m²)

Usually in stock

Suitable for interior and domestic exterior walls and floors.

CA' PIETRA

CAPIETRA.COM



WALNUT



OAK



NATURAL

TECHNICAL DATA

TEST	STANDARD	RESULT
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	≤0.5%
Modulus of Rupture	EN ISO 10545-4	32N/mm ²
Resistance to Crazeing	EN ISO 10545-11	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - High Concentrations	EN ISO 10545-13	GHA
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	GA
Stain Resistance	EN ISO 10545-14	5
Resistance to Fire	EN 9239-1	A1
Slip Rating	DIN 51130	Class 2
Slip Rating - Barefoot	DIN 51130	R10
Dynamic Coefficient of Friction	ANSI A137	>0.42

Rectified: YES NO

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

PRODUCT NOTES

Please refer to our 'Understanding Unrectified Porcelain Tiles' sheet on our website for product installation advice.

