


PROVENCE

PORCELAIN - MATT OR TEXTURED

Previously known as Nimes

Replicating slight undulations found in French antique flagstones, these tiles reflect the idea of the passage of time leaving its mark. With a tonal range suitable for contemporary, natural interiors and heritage properties alike.



Credit: Langton Homes

TALCO 60.4 X 90.6 X 1CM



CENERE PAVING



CENERE, MIX OF ALL THREE 1CM THICK SIZES



TALCO PAVING

FORMAT (CM)

30.2 x 60.4 x 1
60.4 x 60.4 x 1
60.4 x 90.6 x 1
60.4 x 90.6 x 2 (paving)

FINISH

Matt
Matt
Matt
Textured

SOLD BY

6 pieces (1.094m²)
4 pieces (1.459m²)
3 pieces (1.641m²)
1 piece (0.547m²)

AVAILABILITY

Usually in stock
Usually in stock
Usually in stock
Usually in stock

NOTES

1cm thick tiles: Suitable for interior walls and floors.
Paving: Suitable for exterior floors, pool surrounds.

TALCO



30.2 X 60.4 X 1CM



60.4 X 60.4 X 1CM



60.4 X 90.6 X 1CM



60.4 X 90.6 X 2CM (PAVING)

CENERE



30.2 X 60.4 X 1CM



60.4 X 60.4 X 1CM



60.4 X 90.6 X 1CM



60.4 X 90.6 X 2CM (PAVING)

TECHNICAL DATA

TEST	STANDARD	RESULT
Sizing	-	Nominal size: 60.4 x 60.4cm Final rectified size: 60 x 60cm Nominal size: 60.4 x 90.6cm Final rectified size: 60 x 90.15cm Nominal size: 30.2 x 60.4cm Final rectified size: 29.85 x 60cm
Number of Faces	-	Cenere 30.2 x 60.4 x 1cm: 43 Cenere 60.4 x 60.4 x 1cm: 23 Cenere 60.4 x 90.6 x 1cm: 23 Cenere Paving 60.4 x 90.6 x 2cm: 23 Talco 30.2 x 60.4 x 1cm: 50 Talco 60.4 x 60.4 x 1cm: 25 Talco 60.4 x 90.6 x 1cm: 25 Talco Paving 60.4 x 90.6 x 2cm: 25
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	1cm thick tiles: $\leq 0.5\%$ Paving: 0.2%
Modulus of Rupture	EN ISO 10545-4	$\geq 35\text{N/mm}^2$
Breaking Strength	EN ISO 10545-4	1cm thick tiles: $\geq 1300\text{N}$ Paving: 10000N
Deep Abrasion Resistance	EN ISO 10545-6	1cm thick tiles: $\leq 175\text{mm}^3$ Paving: 145mm ³
Superficial Abrasion Resistance	EN ISO 10545-7	Class 4
Resistance to Crazing	EN ISO 10545-11	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - High Concentrations	EN ISO 10545-13	Resistant
Chemical Resistance - Low Concentration	EN ISO 10545-13	Resistant
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	1cm thick tiles: UB Paving: UA
Stain Resistance	EN ISO 10545-14	≥ 3
Resistance to Fire	EN 9239-1	A1
Slip Rating - Critical Angle	DIN 51097	Paving: A+B
Slip Rating - Barefoot	DIN 51130	1cm thick tiles: R10 Paving: R11
Dynamic Coefficient of Friction	ANSI A137	Paving: >0.4

Rectified: YES NO

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

**UK
CA**

CA' PIETRA

CAPIETRA.COM