


WYCHWOOD CLAIRE

PORCELAIN - MATT OR TEXTURED

The sister to our Wychwood Porcelain, Wychwood Claire offers a more contemporary, lighter feel to the original tone- offering a clean, neutral feel that sets the tone for your space; whilst being filled with character, thanks to the scattered fossils and aged-looking, wavy tile edge.



60 X 90 X 1CM



PAVING

FORMAT (CM)	FINISH	SOLD BY	AVAILABILITY	NOTES
60 x 90 x 1	Matt	3 pieces (1.62m ²)	Usually in stock	1cm thick tiles: Suitable for interior walls and floors.
60 x 90 x 2 (Paving)	Textured	2 pieces (1.08m ²)	Usually in stock	Paving: Suitable for exterior floors, pool surrounds



60 X 90 X 1CM



60 X 90 X 2CM (PAVING)

TECHNICAL DATA

TEST	STANDARD	RESULT
Number of Faces	-	9
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	≤ 0.5%
Modulus of Rupture	EN ISO 10545-4	≥ 40 N/mm ²
Breaking Strength	EN ISO 10545-4	1cm thick tiles: 1500N Paving: 8000 N
Thermal Shock Resistance	EN ISO 10545-9	Resistant
Resistance to Crazeing	EN ISO 10545-11	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	GB
Resistance to Fire	EN 9239-1	A1
Hardness (MOHS)	UNE 67101	5
Slip Rating	DIN 51130	1cm thick tiles: Class 2 Paving: Class 3
Slip Rating - Critical Angle	DIN 51097	1cm thick tiles: A+B Paving: A+B+C
Slip Rating - Barefoot	DIN 51130	1cm thick tiles: R10 Paving: R11

Rectified: YES NO

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to our 'Understanding Unrectified Porcelain Tiles' sheet on our website for product installation advice.

**UK
CA**

CA' PIETRA

CAPIETRA.COM