


CHATHAM

PORCELAIN - MATT

Previously known as Southwold

These classic wood effect porcelain tiles look equally as stylish in a bathroom as they do a hallway. Open up a home by laying them throughout the whole ground floor of a project.



FORMAT (CM)	SOLD BY	AVAILABILITY	NOTES
9.8 x 50 x 0.9	16 pieces (0.784m ²)	Usually in stock	Suitable for interior and domestic exterior walls and floors.

CA' PIETRA


CAPIETRA.COM



WALNUT



OAK



NATURAL

TECHNICAL DATA

TEST	STANDARD	RESULT
Sizing	-	30
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	≤0.5%
Modulus of Rupture	EN ISO 10545-4	32N/mm ²
Resistance to Crazing	EN ISO 10545-11	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - High Concentrations	EN ISO 10545-13	GHA
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	GA
Stain Resistance	EN ISO 10545-14	5
Resistance to Fire	EN 9239-1	A1
Slip Rating	DIN 51130	Class 2
Slip Rating - Barefoot	DIN 51130	R10
Dynamic Coefficient of Friction	ANSI A137	>0.42
Pendulum Test Value (Dry)*	EN 16165	PTV 71.1
Pendulum Test Value (Wet)*	EN 16165	PTV 55.5

*Pendulum test (Annex C) using Slider 96.

Rectified: YES ☐ NO ☒

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

PRODUCT NOTES

Please refer to our 'Understanding Unrectified Porcelain Tiles' sheet on our website for product installation advice.

UK
CA

CA' PIETRA

CAPIETRA.COM