


ISLE

PORCELAIN - MATT

Previously known as Abbotsbury

This wonderful, authentic-looking, high-definition porcelain tile is inspired by classic English limestone. The collection is perfect for floors and walls in both classic and modern interiors.



PERLA 60 X 90 X 1CM



SABBIA 30 X 60 X 1CM



CREMA 60 X 90 X 1CM

FORMAT (CM)	SOLD BY	AVAILABILITY	NOTES
29.7 x 59.7 x 1	6 pieces (1.064m ²)	Usually in stock	Suitable for interior walls and floors.
59.7 x 59.7 x 1	3 pieces (1.069m ²)	Usually in stock	
59.7 x 89.5 x 1	2 pieces (1.068m ²)	Usually in stock	


CA' PIETRA

CAPIETRA.COM


CREMA



30 x 60 x 1cm




60 x 60 x 1cm




60 x 90 x 1cm


PERLA



30 x 60 x 1cm




60 x 60 x 1cm




60 x 90 x 1cm


SABBIA



30 x 60 x 1cm



60 x 60 x 1cm



60 x 90 x 1cm

TECHNICAL DATA

TEST	STANDARD	RESULT
Number of Faces	-	29.7 x 59.7 x 1cm: 28 59.7 x 59.7 x 1cm: 14 59.7 x 89.5 x 1cm: 9
Sizing	-	Nominal size: 30 x 60cm: Final rectified size: 29.7 x 59.7cm Nominal size: 60 x 60cm: Final rectified size: 59.7 x 59.7cm Nominal size: 60 x 90cm: Final rectified size: 59.7 x 89.5
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	≤0.5%
Modulus of Rupture	EN ISO 10545-4	≥35N/mm ²
Breaking Strength	EN ISO 10545-4	≥1300N
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	Pass
Resistance to Fire	EN 9239-1	A1
Slip Rating - Critical Angle	DIN 51097	A+B
Slip Rating - Barefoot:	DIN 51130	R10

Rectified: YES ☒ NO ☐

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

**UK
CA**

CA' PIETRA

CAPIETRA.COM