


LOUVRE

PORCELAIN - MATT

Previously known as Monolith

A stunning matt, textured finish concrete-effect porcelain, Louvre creates a uniform effect throughout. Its cloudy palette has the look and tactile feel of a natural material, ideal for achieving a high-spec interior on a budget.



BLANC 60 X 120 X 1CM



PERLA 60 X 120 X 1CM

FORMAT (CM)	SOLD BY	AVAILABILITY	NOTES
80 x 80 x 1	2 pieces (1.28m ²)	Usually in stock	Suitable for interior walls and floors.
60 x 120 x 1	2 pieces (1.44m ²)	Usually in stock	

CA' PIETRA

CAPIETRA.COM




BLANC 60 X 120 X 1CM



BLANC 80 X 80 X 1CM



PERLA 80 X 80 X 1CM



PERLA 60 X 120 X 1CM

TECHNICAL DATA

TEST	STANDARD	RESULT
Number of Faces	-	60 x 120 x 1cm: 7 80 x 80 x 1cm: 9
Sizing	-	Nominal size: 60 x 120cm Nominal size: 80 x 80cm Final rectified size: 60 x 120cm Final rectified size: 80 x 80cm
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	<0.5%
Modulus of Rupture	EN ISO 10545-4	≥35N/mm ²
Breaking Strength	EN ISO 10545-4	≥1300N
Superficial Abrasion Resistance	EN ISO 10545-7	Class 2
Linear Thermal Expansion	EN ISO 10545-8	<9.0 x 10 ⁻⁶ °C ⁻¹
Thermal Shock Resistance	EN ISO 10545-9	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - High Concentrations	EN ISO 10545-13	Resistant
Chemical Resistance - Low Concentration	EN ISO 10545-13	HA
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	LB
Stain Resistance	EN ISO 10545-14	A
Resistance to Fire	EN 9239-1	5
Scratch Resistance	EN 101	A1
Slip Rating - Critical Angle	DIN 51097	Class 2
Slip Rating - Barefoot	DIN 51130	C
Slip Rating	BS 7976-2	R10
Dynamic Coefficient of Friction	ANSI A137	≥0.36

Rectified: YES ☒ NO ☐

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

**UK
CA**

CA' PIETRA

CAPIETRA.COM