


# PIERRE

PORCELAIN - TEXTURED

Previously known as Bordeaux

A timeless replication of limestone floors typically found in a French château; Pierre imitates the signs of authentic wearing over the years. The undulated edges and high tonal variance reinforce the natural, reclaimed effect.



GRIS 59.8 X 89.8 X 1CM



GRIS PAVING



BEIGE



BEIGE PAVING

| FORMAT (CM)              | SOLD BY                         | AVAILABILITY     | NOTES                                                    |
|--------------------------|---------------------------------|------------------|----------------------------------------------------------|
| 59.8 x 89.8 x 1          | 2 pieces (1.074m <sup>2</sup> ) | Usually in stock | 1cm thick tiles: Suitable for interior walls and floors. |
| 59.8 x 89.8 x 2 (Paving) | 1 piece (0.537m <sup>2</sup> )  | Usually in stock | Paving: Suitable for exterior floors, pool surrounds.    |

## CA' PIETRA

CAPIETRA.COM



BEIGE



BEIGE PAVING



GRIS



GRIS PAVING

## TECHNICAL DATA

| TEST                                                     | STANDARD        | RESULT                                                                                          |
|----------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------------------|
| Nominal Size                                             | -               | 60 x 90cm                                                                                       |
| Final Rectified Size                                     | -               | 59.8 x 89.8cm                                                                                   |
| Number of Faces                                          | -               | 12                                                                                              |
| Dimensional Tolerances                                   | EN ISO 10545-2  | Within standard tolerances                                                                      |
| Water Absorption                                         | EN ISO 10545-3  | 1cm thick tiles: $\leq 0.5\%$<br>Paving: $\leq 0.1\%$                                           |
| Modulus of Rupture                                       | EN ISO 10545-4  | 1cm thick tiles: $\geq 35\text{N/mm}^2$<br>Paving: $\geq 50\text{N/mm}^2$                       |
| Breaking Strength                                        | EN ISO 10545-4  | 1cm thick tiles: $\geq 1300\text{N}$<br>Paving: 13600N                                          |
| Deep Abrasion Resistance                                 | EN ISO 10545-6  | Paving: $\leq 175\text{mm}^3$                                                                   |
| Linear Thermal Expansion                                 | EN ISO 10545-8  | 1cm thick tiles: $7 \times 10^{-6} \text{C}^{-1}$<br>Paving: $< 9 \times 10^{-6} \text{C}^{-1}$ |
| Thermal Shock Resistance                                 | EN ISO 10545-9  | Resistant                                                                                       |
| Resistance to Crazeing                                   | EN ISO 10545-11 | 1cm thick tiles: Resistant                                                                      |
| Frost Resistance                                         | EN ISO 10545-12 | Resistant                                                                                       |
| Chemical Resistance - High Concentrations                | EN ISO 10545-13 | Paving: HA                                                                                      |
| Chemical Resistance - Low Concentration                  | EN ISO 10545-13 | Paving: LA                                                                                      |
| Chemical Resistance - Households/Swimming Pool Chemicals | EN ISO 10545-13 | 1cm thick tiles: GB<br>Paving: B                                                                |
| Stain Resistance                                         | EN ISO 10545-14 | 1cm thick tiles: 3<br>Paving: 5                                                                 |
| Resistance to Fire                                       | EN 9239-1       | A1                                                                                              |
| Hardness (MOHS)                                          | UNE 67101       | 1cm thick tiles:                                                                                |
| Slip Rating - Critical Angle                             | DIN 51097       | Paving: A+B                                                                                     |
| Slip Rating - Barefoot                                   | DIN 51130       | 1cm thick tiles: R10<br>Paving: R11                                                             |
| Slip Rating                                              | BS 7976-2       | Paving: PTV +36 (Wet)                                                                           |
| Dynamic Coefficient of Friction                          | ANSI A137       | Paving: $> 0.4$                                                                                 |

Rectified: YES ☒ NO ☐

For any further information or advice, please contact our team.

## INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.



# CA' PIETRA

CAPIETRA.COM