


# PORTARE CANERO

CERAMIC - MATT

Taking its cues from old French tiles, Canero has an authentically aged-looking effect, creating a soft, subtle pattern that's a dream to care for. This tile comes as a larger tile with a prescored grout joint down the centre, designed to give the effect of smaller tiles in a more cost-effective way.



FORMAT (CM)

45 x 45 x 0.9

SOLD BY

6 pieces (1.22m<sup>2</sup>)

AVAILABILITY

Usually in stock

NOTES

Suitable for interior walls and floors.

## CA' PIETRA

Portare Collection

[CAPIETRA.COM](https://www.capietra.com)



SHOWN GROUTED

## TECHNICAL DATA

| TEST                                                     | STANDARD        | RESULT                     |
|----------------------------------------------------------|-----------------|----------------------------|
| Dimensional Tolerances                                   | EN ISO 10545-2  | Within standard tolerances |
| Water Absorption                                         | EN ISO 10545-3  | 3-6%                       |
| Modulus of Rupture                                       | EN ISO 10545-4  | >22N/mm <sup>2</sup>       |
| Breaking Strength                                        | EN ISO 10545-4  | >1000N                     |
| Superficial Abrasion Resistance                          | EN ISO 10545-7  | Class 4                    |
| Thermal Shock Resistance                                 | EN ISO 10545-9  | Resistant                  |
| Resistance to Crazeing                                   | EN ISO 10545-11 | Resistant                  |
| Chemical Resistance - High Concentrations                | EN ISO 10545-13 | HA                         |
| Chemical Resistance - Low Concentration                  | EN ISO 10545-13 | LA                         |
| Chemical Resistance - Households/Swimming Pool Chemicals | EN ISO 10545-13 | A                          |
| Stain Resistance                                         | EN ISO 10545-14 | 5                          |
| Resistance to Fire                                       | EN 9239-1       | A                          |
| Hardness (MOHS)                                          | UNE 67101       | N                          |
| Slip Rating - Barefoot                                   | DIN 51130       | R9                         |
| Slip Rating                                              | BS 7976-2       | PTV +36 (Wet)              |
| Dynamic Coefficient of Friction                          | ANSI A137       | >0.42                      |

Rectified: YES ☐ NO ☒

For any further information or advice, please contact our team.

## INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

## PRODUCT NOTES

Please note, these tiles are prescored and require grout to be applied into the lines cut into the tile surface to give the correct effect.