


PURBECK

PORCELAIN - MATT

Previously known as Ammonite

This soft beige-toned porcelain gives an organic and natural ambience for a perfectly elegant backdrop to any space.



FORMAT (CM)

SOLD BY

AVAILABILITY

NOTES

60 x 120 x 1

2 pieces (1.44m²)

Usually in stock

Suitable for interior walls and floors.

CA' PIETRA

CAPIETRA.COM



60 X 120 X 1CM

TECHNICAL DATA

TEST	STANDARD	RESULT
Number of Faces	-	8
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	≤0.5%
Modulus of Rupture	EN ISO 10545-4	≥35N/mm ²
Breaking Strength	EN ISO 10545-4	≥1300N
Impact Resistance	EN ISO 10545-5	0.9
Superficial Abrasion Resistance	EN ISO 10545-7	Class 4
Linear Thermal Expansion	EN ISO 10545-8	(5.7/5.9) x 10 ⁻⁶ °C ⁻¹
Thermal Shock Resistance	EN ISO 10545-9	Resistant
Moisture Expansion	EN ISO 10545-10	0.0mm/m
Resistance to Crazeing	EN ISO 10545-11	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - High Concentrations	EN ISO 10545-13	HB
Chemical Resistance - Low Concentration	EN ISO 10545-13	LB
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	B
Stain Resistance	EN ISO 10545-14	3
Resistance to Fire	EN 9239-1	A1
Slip Rating - Critical Angle	DIN 51097	A+B
Slip Rating - Barefoot	DIN 51130	R10
Dynamic Coefficient of Friction	ANSI A137	>0.42

Rectified: YES ☒ NO ☐

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

**UK
CA**

CA' PIETRA

CAPIETRA.COM