


SOUTHDOWN

PORCELAIN - SATIN

The ideal tone for any space - the creamy, aged-stone effect pairs with almost any style, and is a dream to care for.



60 X 60 X 0.9CM (WALL), 60 X 120 X 0.9CM (FLOOR)
SHOWN WITH HAMMAN




PAVING

FORMAT (CM)	SOLD BY	AVAILABILITY	NOTES
60 x 60 x 0.9	4 pieces (1.44m ²)	Usually in stock	0.9cm thick tiles: Suitable for interior walls and floors. Paving: Suitable for exterior floors, pool surrounds.
60 x 120 x 0.9	2 pieces (1.44m ²)	Usually in stock	
60 x 90 x 2 (paving)	1 piece (0.54m ²)	Usually in stock	

CA' PIETRA


CAPIETRA.COM



60 X 120 X 1CM



60 X 60 X 1CM



PAVING: 60 X 90 X 2CM

TECHNICAL DATA

TEST	STANDARD	RESULT
Sizing	-	Nominal size: 60 x 60cm Nominal size: 60 x 120cm Nominal size: 60 x 90cm Final rectified size: 60 x 60cm Final rectified size: 60 x 120cm Final rectified size: 60 x 90cm
Number of Faces	-	Paving 60 x 90 x 2cm: 6 60 x 120 x 0.9cm: 4 60 x 60 x 0.9cm: 8
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	IS 13630-2	0.9cm thick tiles: 0.06% Paving: ≤ 0.5 %
Modulus of Rupture	IS 13630-6	0.9cm thick tiles: >40N/mm ² Paving: 42 N/mm ²
Breaking Strength	IS 13630-6	0.9cm thick tiles: >1700N Paving: 1300 N
Impact Resistance	EN ISO 10545-5	Paving: >0.55
Superficial Abrasion Resistance	IS 13630-11	0.9cm thick tiles: 5
Linear Thermal Expansion	IS 13630-4	0.9cm thick tiles: 6x10 ⁻⁶ k-1 Paving: < 9.0 x 10 ⁻⁶ °C-1
Thermal Shock Resistance	EN ISO 10545-9	Paving: Resistant 0.9cm thick tiles: 10 Cycles
Resistance to Crazeing	EN ISO 10545-11	Paving: Resistant
Frost Resistance	IS 13630-10	Resistant
Household Chemicals	IS 13630-8	AA
Acid Resistance	IS 13630-8	Resistant
Stain Resistance	IS 13630-8	Resistant
Resistance to Fire	EN 9239-1	A1
Hardness (MOHS)	UNE 67101	0.9cm thick tiles: 5
Slip Rating - Barefoot	DIN 51130	0.9cm thick tiles: R9 Paving: R11

Rectified: YES ☒ NO ☐

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

**UK
CA**

CA' PIETRA

CAPIETRA.COM