


TRAFALGAR

SANDSTONE - ETCHED/TUMBLED

A smooth, homogeneous ivory-greige European sandstone, with exceptionally fine grain for superior weather resistance.



PAVING



COBBLES



KLINKERS



BULLNOSE COPING

OPTION	FORMAT (CM)	AVAILABILITY	NOTES
Paving	60 x 90 x 3cm (Etched)	Usually in stock	Suitable for external paving, pool surrounds, sealing required. Klinkers are suitable for external paving, driveways.
Cobbles	14 x Random x 4cm (Tumbled)	Usually in stock	
Klinkers	5 x 20 x 4cm (Tumbled)	Usually in stock	
Bullnosed Coping	40 x 100 x 4cm (Etched)	Usually in stock	

Bespoke options available.

CA' PIETRA

CAPIETRA.COM

TECHNICAL DATA

TEST	STANDARD	RESULT
Apparent Density	BS EN 1936 : 2006	2360kg/m ³
Open Porosity	BS EN 1936 : 2006	12.5%
Water Absorption at Atmospheric Pressure	BS EN 13755 : 2008	5.2%
Flexural Strength (3 Point)	BS EN 12372 : 2006	9.7MPa
Frost Resistance (56 Cycles)	BS EN 12371 : 2010	9.3MPa
Abrasion Resistance	BS EN 14157 : 2004	37.5mm
Compressive Strength	BS EN 1926 : 2006	77MPa
Slip Resistance (Etched) (Dry)	BS EN 14231 : 2003	PTV 96

- ✓ Suitable for use in wet areas
- ✓ Suitable for use in freezing temperatures

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.

PRODUCT NOTES

When used externally, the appearance of this stone will change over time. For more information on this, please see the info sheet 'Understanding Weathering of Natural Stone' on our website.