


WANSDYKE

EXTERNAL TERRACOTTA - NATURAL

Thanks to a rare blend of minerals contained within the clay used to make this tile, this Italian-made terracotta tile is extremely hard and durable, suitable even for harsh winter frosts.



FORMAT (CM)

Parquet: 7 x 28 x 1.5

AVAILABILITY

Usually in stock

NOTES

Suitable for interior walls and floors, external paving, pool surrounds, sealing required.

CA' PIETRA

CAPIETRA.COM

TECHNICAL DATA

TEST	STANDARD	RESULT
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water absorption	UNI EN ISO 10545-3	Compliant
Breaking strenght	UNI EN ISO 10545-4	> 800N
Modulus of rupture	UNI EN ISO 10545-4	> 13N/mm ²
Abrasion resistance	UNI EN ISO 10545-6	< 500mm ³
Linear thermal expansion	UNI EN ISO 10545-8	$\alpha(1) = 6,3 \times 10^{-6} \text{ }^{\circ}\text{C}^{-1}$ $\alpha(2) = 6,5 \times 10^{-6} \text{ }^{\circ}\text{C}^{-1}$
Moisture expansion	UNI EN ISO 10545-10	< 0,02
Thermal shock resistance	UNI EN ISO 10545-9	Resistant
Frost resistance	UNI EN ISO 10545-12	Resistant
Impact resistance	UNI EN ISO 10545-5	> 0,55
Resistance to low concentrations of acids and alkalis	UNI EN ISO 10545-13	LA (KOH 3%) LB (HCl 3%) LC (Citric acid solution 10%)
Resistance to household chemicals and swimming pool salts	UNI EN ISO 10545-13	A
Slip Resistance (Dry)	BS EN 14231 : 2003	PTV 66.6
Slip Resistance (Wet)	BS EN 14231 : 2003	PTV 61.7
Slip Test - Shod	DIN EN 16165-B	R12
Resistance to light	DIN 51094	Resistant

- ✓ Suitable for use with underfloor heating
- ✓ Suitable for use in wet areas
- ✓ Suitable for use in freezing temperatures

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please refer to the installation guides on our website.