


ZAHARA

PORCELAIN - MATT

A flawless copy of veincut travertine, this warm, creamy, sandy-beige tile replicates all of the subtle texture variance and texture of the real thing in an easy-to-maintain porcelain format. Combine with the two unique mosaic options for truly unique designs!



ZAHARA AND ZAHARA ARCH MOSAIC
SHOWN WITH PLASTERCRAFT LINEA MANO ECRU



ZAHARA

OPTION	FORMAT (CM)	SHEETS/M ²	SOLD BY	AVAILABILITY	NOTES
Tile	29.3 x 59.3 x 0.8	-	7 pieces (1.22m ²)	Usually in stock	Suitable for interior walls and floors.
Tile	60 x 120 x 1.1	-	2 pieces (1.44m ²)	Usually in stock	
Bamboo Mosaic	29.3 x 29.3 x 0.8	1.65	Sheet (0.09m ²)	Usually in stock	
Arch Mosaic	30 x 30 x 0.8	11.11	Sheet (0.09m ²)	Usually in stock	

CA' PIETRA

CAPIETRA.COM



29.3 X 59.3 X 0.8CM



60 X 120 X 1.1CM

BAMBOO MOSAIC
29.3 X 29.3 X 0.8CMARCH MOSAIC
30 X 30 X 0.8CM

TECHNICAL DATA

TEST	STANDARD	RESULT
Sizing	-	Nominal size: 30 x 60cm Nominal size: 60 x 120cm Final rectified size: 29.3 x 59.3cm Final rectified size: 60 x 120cm
Number of Faces	-	29.3 x 59.3 x 0.8cm: 50 60 x 120 x 1.1cm: 12
Dimensional Tolerances	EN ISO 10545-2	Within standard tolerances
Water Absorption	EN ISO 10545-3	< 0.5%
Modulus of Rupture	EN ISO 10545-4	> 35N/mm ²
Breaking Strength	EN ISO 10545-4	>1300N
Superficial Abrasion Resistance	EN ISO 10545-7	Class 4
Linear Thermal Expansion	EN ISO 10545-8	< 8 x 10 ⁻⁶ °C
Thermal Shock Resistance	EN ISO 10545-9	Resistant
Frost Resistance	EN ISO 10545-12	Resistant
Chemical Resistance - High Concentrations	EN ISO 10545-13	Resistant
Chemical Resistance - Low Concentration	EN ISO 10545-13	LB
Chemical Resistance - Households/Swimming Pool Chemicals	EN ISO 10545-13	A
Stain Resistance	EN ISO 10545-14	4
Resistance to Fire	EN 9239-1	A1
Slip Rating	DIN 51130	Class 1
Slip Rating - Barefoot	DIN 51130	R10
Slip Rating	BS 7976-2	PTV +36 (Wet)

Rectified: YES ☒ NO ☐

For any further information or advice, please contact our team.

INSTALLATION, CARE & MAINTENANCE ADVICE

Please note that due to the mosaics being mesh-mounted, we would advise the use of a resin-based adhesive. Please refer to the installation guides on our website.

**UK
CA**

CA' PIETRA

CAPIETRA.COM